

Item	AQCT_Item Code	Item Description	Equipment	Manufacture/Brand	Quantity One Shipment	UOM
1	100222	Tire 1100-20-16	Terminal Truck	Size : 1100 – 20 Bias, pneumatic, & tread tire type. Industrial & Inner and tube tire type. 16 PLY Rate Static load not less than 6.8 Ton.	6	Each
2	100223	Tire 1000-20-7.5 Solid / Smooth	Terminal Trailer	Size : 1000 – 20 Solid - smooth tire type. Smooth - Industrial tire. Rim size 7.5 X 20 Static load not less than 6.8 Ton. 4 Ton at 100 km/hr. and 5 Ton at 25 km/hr. at full load.	2	Each
3	100224	Tire 650-10 Solid	Forklift	Size : 650 – 10 Solid, Tread, Industrial & steer tire type. Rim size 5.00F – 10 10 PLY Rate Static load not less than 1.6 Ton. Speed 12 km/hr. at no load and 11 km/hr. at full load	2	Each
4	100225	Tire 1800-25-40 tread	Reach Stacker	Size : 1800 – 25 Bias, Pneumatic, & Tubeless tire Tread - Industrial tire. Tread depth not less than 62 mm 40 PLY Rate Static load not less than 30 Ton. Air seal shall be included	4	Each
5	100226	Tire 2100 – 25 – 40PR Tread	hRTG	Size: 2100 – 25 Bias, Pneumatic type – Tubeless tire. Tread "RL" – Industrial Port Service Tread depth not less than 39 mm 40 PLY Rate Static load not less than 37 Ton. Air seal shall be included.	2	Each
6	100227	Tire 28 – 9 – 15 Pneumatic - Front Tire	Forklift	Size : 28 – 9 - 15 Bais, Pneumatic, &Tread type tire. Industrial & tire type. Rim size 7.00F – 15 14 PLY Rate Static load not less than 3.95 Ton. Speed 12 km/hr. at no load and 11 km/hr. at full load	2	Each
7	100228	Tire 1200 – 20 - 20PR	ECH	Size : 1200 – 20 Bias, Pneumatic, & Tubeless tire Smooth - Industrial tire. Tread depth not less than 62 mm 40 PLY Rate Static load not less than 30 Ton. Air seal shall be included	2	Each
8	100229	Tire 1400 – 24 - 28PR	eECH	Size: 1400R20 Bias, Pneumatics & inner & tube type. Tread LE29 - Industrial Port Service. Tread depth not less than 37 mm 28 PLY Rate Rim size 10 Max. load not less than 12 Ton.	6	Each

\* Delivery to Abuqir Container Terminal - Abuqir Port

Item	AICT Item Code	Item Description	Equipment	Manufacture/Brand	1st batch Quantity	2nd batch Quantity	UOM	Total Quantity
1	1002830	Tire 1800-25-40 tread	Reach Stacker	Size : 1800 – 25 Bias, Pneumatic, & Tubeless tire Tread - Industrial tire. Tread depth not less than 62 mm 40 PLY Rate Static load not less than 30 Ton. Air seal shall be included	20	24	EACH	44
2	1011645	Tire 1100 R 22.5 -16 PR - M840(HDR) / (Mol-TK)	Terminal Truck	Size : 1100-22.5 Bias, Pneumatic, & Tubeless tire Tread - Industrial tire. 16 PLY Rate Max. load single 3150 kg at 120 PSI Position : HDR	80	40	EACH	120
3	1011646	Tire 1100 R 22.5 -16 PR (HSR)- R187 / (Mol-TK)	Terminal Truck	Size : 1100-22.5 Bias, Pneumatic, & Tubeless tire Tread - Industrial tire. 16 PLY Rate Max. load single 3150 kg at 120 PSI Position : HSR	40	20	EACH	60

\*Delivery to Alexandria Port